

Safety Data Sheet

according to Regulation (EC) No. 1907/2006

freeprint® splintmaster flex

Revision date: 05.04.2023

Product code: 2052

Page 1 of 12

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

freeprint® splintmaster flex

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Light curing one component material for the fabrication of dental splints and guides.

1.3. Details of the supplier of the safety data sheet

Company name:	DETAX GmbH	
Street:	Carl-Zeiss-Straße 4	
Place:	D-76275 Ettlingen	
Telephone:	+49 7243/510-0	Telefax: +49 7243/510-100
e-mail:	post@detax.com	
Internet:	www.detax.com	
Responsible Department:	This number is only obtainable during office hours (Monday - Thursday 8.00 a.m. - 5.00 p.m., Friday 8.00 a.m. - 4.00 p.m.)	

1.4. Emergency telephone number:

+1-800-424-9300 (CHEMTREC worldwide)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1907/2006

Skin Irrit. 2; H315
 Eye Irrit. 2; H319
 Skin Sens. 1; H317
 STOT SE 3; H335
 Aquatic Chronic 2; H411

Full text of hazard statements: see SECTION 16.

2.2. Label elements


Regulation (EC) No. 1907/2006

Hazard components for labelling

7,7,9(or 7,9,9)-trimethyl-4,13-dioxo-3,14-dioxo-5,12-diazahexadecane-1,16-diyl bismethacrylate
 (Octahydro-4,7-methano-1H-indenyl)methyl acrylate
 Hydroxy propyl methacrylate
 2-hydroxyethyl methacrylate
 Ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate

Signal word: Warning

Pictograms:



Hazard statements

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H411	Toxic to aquatic life with long lasting effects.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006

freeprint® splintmaster flex

Revision date: 05.04.2023

Product code: 2052

Page 2 of 12

Precautionary statements

P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P302+P352	IF ON SKIN: Wash with plenty of water.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.
P391	Collect spillage.
P501	Dispose of contents/ container in accordance with local and national regulations.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Mixture of acrylic/ methacrylic resins with auxilliary matters.

Hazardous components

CAS No	Chemical name	Quantity
	EC No	
	Index No	
	REACH No	
	Classification (Regulation (EC) No. 1907/2006)	
72869-86-4	7,7,9(or 7,9,9)-trimethyl-4,13-dioxo-3,14-dioxa-5,12-diazahexadecane-1,16-diyl bismethacrylate	40 - < 60 %
	276-957-5	01-2120751202-68
	Skin Sens. 1B, Aquatic Chronic 2; H317 H411	
93962-84-6	(Octahydro-4,7-methano-1H-indenyl)methyl acrylate	20 - < 40 %
	300-723-4	01-2120785023-58
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1B, STOT SE 3, Aquatic Chronic 2; H315 H319 H317 H335 H411	
27813-02-1	Hydroxy propyl methacrylate	5 - < 20 %
	248-666-3	01-2119490226-37
	Eye Irrit. 2, Skin Sens. 1; H319 H317	
41637-38-1	Ethoxylated bisphenol A dimethacrylate	0.1 - < 5 %
	Aquatic Chronic 4; H413	
868-77-9	2-hydroxyethyl methacrylate	0.1 - < 5 %
	212-782-2	607-124-00-X
	01-2119490169-29	
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1; H315 H319 H317	
84434-11-7	Ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate	0.1 - < 5 %
	282-810-6	01-2119987994-10
	Skin Sens. 1B, Aquatic Chronic 2; H317 H411	

Full text of H and EUH statements: see section 16.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006

freeprint® splintmaster flex

Revision date: 05.04.2023

Product code: 2052

Page 3 of 12

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
72869-86-4	276-957-5	7,7,9(or 7,9,9)-trimethyl-4,13-dioxo-3,14-dioxa-5,12-diazahexadecane-1,16-diyl bismethacrylate	40 - < 60 %
		dermal: LD50 = >2000 mg/kg; oral: LD50 = >5000 mg/kg	
93962-84-6	300-723-4	(Octahydro-4,7-methano-1H-indenyl)methyl acrylate	20 - < 40 %
		oral: LD50 = 2000 mg/kg	
27813-02-1	248-666-3	Hydroxy propyl methacrylate	5 - < 20 %
		dermal: LD50 = >5000 mg/kg; oral: LD50 = >2000 mg/kg	
41637-38-1		Ethoxylated bisphenol A dimethacrylate	0.1 - < 5 %
		dermal: LD50 = 2000 mg/kg; oral: LD50 = 2000 mg/kg	
868-77-9	212-782-2	2-hydroxyethyl methacrylate	0.1 - < 5 %
		dermal: LD50 = >5000 mg/kg; oral: LD50 = 5564 mg/kg	
84434-11-7	282-810-6	Ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate	0.1 - < 5 %
		dermal: LD50 = >2000 mg/kg; oral: LD50 = >5000 mg/kg	

SECTION 4: First aid measures

4.1. Description of first aid measures

After inhalation

Provide fresh air. When in doubt or if symptoms are observed, get medical advice.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. Medical treatment necessary.

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

After ingestion

Rinse mouth immediately and drink 1 glass of water.

Seek immediately medical advice. Do not induce vomiting. In case of spontaneous vomiting take care of an unhindered flow out of the vomit (danger of suffocation).

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.

5.2. Special hazards arising from the substance or mixture

Non-flammable.

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit.

Additional information

Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately.

Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

Safety Data Sheet

according to Regulation (EC) No. 1907/2006

freeprint® splintmaster flex

Revision date: 05.04.2023

Product code: 2052

Page 4 of 12

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

For cleaning up

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Advice on protection against fire and explosion

No special fire protection measures are necessary.

Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep locked up. Store in a place accessible by authorized persons only. Provide adequate ventilation as well as local exhaust at critical locations.

Hints on joint storage

Keep away from spontaneous flammable or combustible substances.

Further information on storage conditions

Keep only in the original container in a dry and well-ventilated place, away from foodstuffs. Keep away from all kind of light. An inert gas blanket should not be applied, because the stability of the product depends on the presence of oxygen (air).

7.3. Specific end use(s)

Light curing material for fabrication of dental splints and guides.

For use by trained specialist staff.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.2. Exposure controls

Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Individual protection measures, such as personal protective equipment

Safety Data Sheet

according to Regulation (EC) No. 1907/2006

freeprint® splintmaster flex

Revision date: 05.04.2023

Product code: 2052

Page 5 of 12

Eye/face protection

Suitable eye protection: goggles.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Suitable are gloves of the following material: Butyl caoutchouc (butyl rubber)

Skin protection

Use of protective clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	liquid:		
Colour:	clear		
Odour:	faintly like esters		
			Test method
Melting point/freezing point:		not determined	
Boiling point or initial boiling point and boiling range:		not determined	
Flammability			
Solid/liquid:		not applicable	
Gas:		not applicable	
Lower explosion limits:		not determined	
Upper explosion limits:		not determined	
Flash point:		>100 °C	DIN 51755
Auto-ignition temperature:		not determined	
Decomposition temperature:		>=190 °C	
pH-Value:		not determined	
Water solubility:		The study does not need to be conducted because the substance is known to be insoluble in water.	
Solubility in other solvents			
not determined			
Partition coefficient n-octanol/water:		not determined	
Vapour pressure:		<1 hPa	
(at 20 °C)			
Density (at 20 °C):		1,09 g/cm ³	DIN 51757
Relative vapour density:		not determined	

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

The product is not: Explosive.

Oxidizing properties

The product is not: oxidising.

Other safety characteristics

Evaporation rate: not determined

Solid content: not determined

Safety Data Sheet

according to Regulation (EC) No. 1907/2006

freeprint® splintmaster flex

Revision date: 05.04.2023

Product code: 2052

Page 6 of 12

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Reacts with : strong oxidising agents, strong alkaline or acidic materials.

10.4. Conditions to avoid

Ultra-violet light and daylight initiate polymerisation of the product. Therefore keep only in tightly closed containers away from any sources of light at 15°C - 28°C / 59°F - 82 °F.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No. 1907/2006

Acute toxicity

Based on available data, the classification criteria are not met.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006

freeprint® splintmaster flex

Revision date: 05.04.2023

Product code: 2052

Page 7 of 12

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
72869-86-4	7,7,9(or 7,9,9)-trimethyl-4,13-dioxo-3,14-dioxa-5,12-diazahexadecane-1,16-diyl bismethacrylate				
	oral	LD50 mg/kg	>5000	Rat	OECD 401
	dermal	LD50 mg/kg	>2000	Rat	OECD 402
93962-84-6	(Octahydro-4,7-methano-1H-indenyl)methyl acrylate				
	oral	LD50 mg/kg	2000	Rat	OECD 423
27813-02-1	Hydroxy propyl methacrylate				
	oral	LD50 mg/kg	>2000	Rat	OECD 401
	dermal	LD50 mg/kg	>5000	Rabbit	
41637-38-1	Ethoxylated bisphenol A dimethacrylate				
	oral	LD50 mg/kg	2000	Rat	OECD 423
	dermal	LD50 mg/kg	2000	Rat	OECD 402
868-77-9	2-hydroxyethyl methacrylate				
	oral	LD50 mg/kg	5564	Rat	
	dermal	LD50 mg/kg	>5000	Rabbit	
84434-11-7	Ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate				
	oral	LD50 mg/kg	>5000	Rat	OECD 401
	dermal	LD50 mg/kg	>2000	Rat	

Irritation and corrosivity

Causes skin irritation.

Causes serious eye irritation.

Sensitising effects

May cause an allergic skin reaction. (7,7,9(or 7,9,9)

-trimethyl-4,13-dioxo-3,14-dioxa-5,12-diazahexadecane-1,16-diyl bismethacrylate;

(Octahydro-4,7-methano-1H-indenyl)methyl acrylate; Hydroxy propyl methacrylate; 2-hydroxyethyl methacrylate; Ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate)

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause respiratory irritation. ((Octahydro-4,7-methano-1H-indenyl)methyl acrylate)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Further information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

Safety Data Sheet

according to Regulation (EC) No. 1907/2006

freeprint® splintmaster flex

Revision date: 05.04.2023

Product code: 2052

Page 8 of 12

SECTION 12: Ecological information

12.1. Toxicity

Toxic to aquatic life with long lasting effects.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
72869-86-4	7,7,9(or 7,9,9)-trimethyl-4,13-dioxo-3,14-dioxo-5,12-diazahexadecane-1,16-diyl bismethacrylate					
	Acute fish toxicity	LC50 mg/l	10,1	96 h		OECD 203
	Acute algae toxicity	ErC50 mg/l	0,21	72 h		OECD 201
	Acute crustacea toxicity	EC50 mg/l	>1,2	48 h	Daphnia magna (Big water flea)	OECD 202
93962-84-6	(Octahydro-4,7-methano-1H-indenyl)methyl acrylate					
	Acute fish toxicity	LC50	1,8 mg/l	96 h	Danio rerio (zebrafish)	OECD 203
	Acute algae toxicity	ErC50 mg/l	1,15	72 h	Pseudokirchneriella subcapitata	OECD 201
	Acute crustacea toxicity	EC50 mg/l	2,64	48 h	Daphnia magna (Big water flea)	OECD 202
27813-02-1	Hydroxy propyl methacrylate					
	Acute fish toxicity	LC50	493 mg/l	96 h	Leuciscus idus (golden orfe)	
	Acute algae toxicity	ErC50 mg/l	>97,2	72 h	Pseudokirchneriella subcapitata	OECD 201
	Acute crustacea toxicity	EC50	380 mg/l	48 h	Daphnia magna (Big water flea)	OECD 202
41637-38-1	Ethoxylated bisphenol A dimethacrylate					
	Acute fish toxicity	LC50 mg/l	>100	96 h	Oncorhynchus mykiss (Rainbow trout)	OECD 203
	Acute algae toxicity	ErC50 mg/l	>100	72 h	Pseudokirchneriella subcapitata	OECD 201
	Acute crustacea toxicity	EC50 mg/l	>100	48 h	Daphnia magna (Big water flea)	OECD 202
868-77-9	2-hydroxyethyl methacrylate					
	Acute fish toxicity	LC50 mg/l	>100	96 h	Oryzias latipes	OECD 203
	Acute algae toxicity	ErC50	836 mg/l	72 h	Selenastrum capricornutum	OECD 201
	Acute crustacea toxicity	EC50	380 mg/l	48 h	Daphnia magna	OECD 202
84434-11-7	Ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate					
	Acute fish toxicity	LC50 mg/l	1,89	96 h	Danio rerio	

12.2. Persistence and degradability

The product has not been tested.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006

freeprint® splintmaster flex

Revision date: 05.04.2023

Product code: 2052

Page 9 of 12

CAS No	Chemical name	Method	Value	d	Source
		Evaluation			
93962-84-6	(Octahydro-4,7-methano-1H-indenyl)methyl acrylate	OECD 301F/ ISO 9408/ EEC 92/69/V, C.4-D	11,8%	28	
	Not readily biodegradable (according to OECD criteria)				
27813-02-1	Hydroxy propyl methacrylate	OECD	94%	28	
	Readily biodegradable (according to OECD criteria).				
41637-38-1	Ethoxylated bisphenol A dimethacrylate	OECD 301D/ EEC 92/69/V, C.4-E	24%	28	
	Not readily biodegradable (according to OECD criteria)				
868-77-9	2-hydroxyethyl methacrylate		92-100%	14	
	Readily biodegradable (according to OECD criteria).				

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
72869-86-4	7,7,9(or 7,9,9)-trimethyl-4,13-dioxo-3,14-dioxa-5,12-diazahexadecane-1,16-diyl bismethacrylate	3,39
27813-02-1	Hydroxy propyl methacrylate	0,97

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

Not identified as PBT/ vPvB substances

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number:

UN 3082

14.2. UN proper shipping name:

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006

freeprint® splintmaster flex

Revision date: 05.04.2023

Product code: 2052

Page 10 of 12

14.3. Transport hazard class(es):	9
14.4. Packing group:	III
Hazard label:	9
Classification code:	M6
Special Provisions:	274 335 375 601
Limited quantity:	5 L
Excepted quantity:	E1
Transport category:	3
Hazard No:	90
Tunnel restriction code:	-

Inland waterways transport (ADN)

14.1. UN number or ID number:	UN 3082
14.2. UN proper shipping name:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
14.3. Transport hazard class(es):	9
14.4. Packing group:	III
Hazard label:	9
Classification code:	M6
Special Provisions:	274 335 375 601
Limited quantity:	5 L
Excepted quantity:	E1

Marine transport (IMDG)

14.1. UN number or ID number:	UN 3082
14.2. UN proper shipping name:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
14.3. Transport hazard class(es):	9
14.4. Packing group:	III
Hazard label:	9
Special Provisions:	274, 335, 969
Limited quantity:	5 L
Excepted quantity:	E1
EmS:	F-A, S-F

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number:	UN 3082
14.2. UN proper shipping name:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
14.3. Transport hazard class(es):	9
14.4. Packing group:	III
Hazard label:	9
Special Provisions:	A97 A158 A197 A215
Limited quantity Passenger:	30 kg G
Passenger LQ:	Y964
Excepted quantity:	E1
IATA-packing instructions - Passenger:	964
IATA-max. quantity - Passenger:	450 L
IATA-packing instructions - Cargo:	964
IATA-max. quantity - Cargo:	450 L

14.6. Special precautions for user

No dangerous good in sense of this transport regulation.

14.7. Maritime transport in bulk according to IMO instruments

No dangerous good in sense of this transport regulation.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Safety Data Sheet

according to Regulation (EC) No. 1907/2006

freeprint® splintmaster flex

Revision date: 05.04.2023

Product code: 2052

Page 11 of 12

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 75

Information according to 2012/18/EU (SEVESO III): E2 Hazardous to the Aquatic Environment

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D): 3 - highly hazardous to water

Skin resorption/Sensitization: Causes allergic hypersensitivity reactions.

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

CLP: Classification, labelling and Packaging

REACH: Registration, Evaluation and Authorization of Chemicals

GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals

UN: United Nations

DNEL: Derived No Effect Level

DMEL: Derived Minimal Effect Level

PNEC: Predicted No Effect Concentration

ATE: Acute toxicity estimate

LL50: Lethal loading, 50%

EL50: Effect loading, 50%

EC50: Effective Concentration 50%

ErC50: Effective Concentration 50%, growth rate

NOEC: No Observed Effect Concentration

BCF: Bio-concentration factor

PBT: persistent, bioaccumulative, toxic

vPvB: very persistent, very bioaccumulative

RID: Regulations concerning the international carriage of dangerous goods by rail

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways (Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures)

EmS: Emergency Schedules

MFAG: Medical First Aid Guide

ICAO: International Civil Aviation Organization

MARPOL: International Convention for the Prevention of Marine Pollution from Ships

IBC: Intermediate Bulk Container

SVHC: Substance of Very High Concern

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

Safety Data Sheet

according to Regulation (EC) No. 1907/2006

freeprint® splintmaster flex

Revision date: 05.04.2023

Product code: 2052

Page 12 of 12

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1907/2006

Classification	Classification procedure
Skin Irrit. 2; H315	Calculation method
Eye Irrit. 2; H319	Calculation method
Skin Sens. 1; H317	Calculation method
STOT SE 3; H335	Calculation method
Aquatic Chronic 2; H411	Calculation method

Relevant H and EUH statements (number and full text)

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H411	Toxic to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)